

<i>Elite 20 ½"</i>	<i>Elite 20 ¾"</i>	<i>TECHNICAL DATA:</i>	<i>Xtreme 40 ¾"</i>	<i>Xtreme 40 1"</i>
739.7 / 29 450 / 17.7 1080 / 42.5		<b>Dimensions mm/inch:</b> Length: Width: Height incl. handle:	795 / 31.3 534 / 21 990 / 38.9	
104 / 230		<b>Weight:</b> kg: / lbs:	117 / 257	
20 / 44.1		<b>Dry Ice Capacity:</b> kg: / lbs:	40 / 88.2	
15 - 100 0.5 - 3.7		<b>Dry Ice Consumption:</b> kg/hr: lbs/min:	45-150 (65-220 optional) 1.1-5.5 (2.4-8.1 optional)	
min 5 - max 16 min 72 - max 232		<b>Supply Pressure:</b> bar: psi:	min 5 - max 16 min 72 - max 232	
min 2 - max 16 min 29 - max 145 (½) max 232 (¾)		<b>Blasting Pressure:</b> bar: psi:	min 2 - max 16 min 29 - max 232	
0.7 - 10 25 - 353		<b>Air Consumption:</b> Nm3/min: cfm: (depending on nozzle combination)	0.7 - 16 25 - 565	
¾" / 1" claw coupling		<b>Compressed Air Connection:</b>	1" claw coupling (1.5" optional)	
According to ISO 8573-1 Class 3 for environment temperature below + 5°C / 41°F		<b>Air Quality:</b>	According to ISO 8573-1 Class 3 for environment temperature below + 5°C / 41°F	
500 W, 90V - 230V AC 50/60 Hz + PE (GND)		<b>Power Consumption:</b>	500 W, 90V - 230V AC 50/60 Hz + PE (GND)	
½" Single Hose System	¾" Single Hose System	<b>Blasting Hose:</b>	¾" Single Hose System	1" Single Hose System
Noise level up to 120 dB[A]. Depending on blasting pressure, nozzle combination and material surface		<b>Noise:</b>	Noise level up to 120 dB[A]. Depending on blasting pressure, nozzle combination and material surface	

<i>Elite 20</i>	<i>Evolution Line Special Features:</i>	<i>Xtreme 40</i>
Insulated hopper for low ice consumption.	<b>Hopper:</b>	Insulated hopper designed for maximum output.
½" Standard HD 7.5m / 24ft hose. ¾" Standard 7.5m / 24ft hose.	<b>Blasting Hose:</b>	Standard 10 / 32ft hose. *HD hose available upon request.
'Slick' full rubber tire wheels for level production floors.	<b>Wheels:</b>	'Terrain' tire wheels pneumatic for easy use in any environment.
Low flow nozzles available.	<b>Nozzles:</b>	Performance nozzles (114.3mm wide).
Collapsible handles integrated with hose hanger.	<b>Handles:</b>	Industrial Strength Collapsible handles.
Located at the back of the machine for easy access.	<b>Airline Purge:</b>	Located at the back of the machine for easy access. Designed with accessible metal handle.
½" Small Light weight Applicator. ¾" Heavy Duty Applicator.	<b>Applicator:</b>	Heavy Duty Applicator.
Steel Black painted rotation locks.	<b>Door Locks:</b>	Vandal-proof, stainless steel door lock.
Light to medium cleaning.	<b>Applications:</b>	Heavy duty / industrial cleaning.
Optional electric vibrator for noise control.	<b>Machine Exclusives:</b>	<ul style="list-style-type: none"> <li>• Empty hopper function.</li> <li>• Foreign particle extraction - performed by the Reverse Dosing Disc function.</li> <li>• IT-3 kit holder (optional).</li> </ul>